



# Animal Management Solutions for Producers

Electric Fencing, Livestock Weighing, EID, Data Management  
& Miraco Watering System Catalog






**COVER:**

**THE NEW M10000I FENCE ENERGIZER WILL DELIVER MORE POWER THAN ANY OTHER ENERGIZER AVAILABLE IN THE WORLD.**

See for yourself innovative new products like the i Series Fence Energizer System - the fence that can't keep a secret! (pages 6-9)



**Producers know that when they purchase a Gallagher product, it comes with a heritage of quality and innovation that has made Gallagher the #1 selling brand of quality animal management products in the world, since 1938.**

# TABLE OF CONTENTS

## POWER SYSTEMS

Energizer Selection Chart	5
110 Volt Energizers	6
Battery Energizers	14
Solar/Battery Energizers	16
Solar Energizers	19
Grounding	22
Power Management Tools	23

## FENCING SYSTEMS

Strainers, End Strain Insulators	24
Wood Post Insulators, Connectors & Clamps	25
Steel & Fiberglass Post Insulators	26
Offsets	27
Cable, Wire Braid & Tape	28
Reels	30
Posts, Pigtailed, Treadins, Fiberglass & Tumblewheels	31
Gates & Accessories	32
Netting & Woven Wire	34
Electric Fence Kits	35
Fence Setups	36
Fence Tools & Accessories	38

## WEIGHING & ELECTRONIC IDENTIFICATION

Weighing & Data Collectors	39
Platforms	45
Loadbars	45
Readers & Accessories	46
Stock Prods & Accessories	48

## MIRACO WATERING TANK SYSTEMS


Mirafount & E-Fount Waterers	50
Lil'Spring Tank Waterers	52
Miraco Installation Diagram	53
EquiFount Waterers	55
BigSpring Tank Waterers	56
Pet Waterer	57
Heaters & Accessories	57



# 4 Electric Fencing Basics

## How Electric Fencing Works

A short, safe and memorable shock to create a psychological as well as a physical barrier.



### PROFITABLE

Maximize pasture growth, minimize feed costs

### SAFE

Animals remember and develop a respect for the fence

### DURABLE

Stock pressure on your fence is reduced so it lasts longer

### EASY TO INSTALL

Less than half the time to build vs a non-electric fence

### ECONOMICAL

Costs less to build and maintain than a non-electric fence

## Getting Started

Every electric fence system is made up of an Energizer, a grounding system and a fence system. Selection of these systems depends on property size, fencing usage and animal type.

**1) What animals do you want to keep in or out?** (See Gallagher Energizer Chart page 5)

**2) Total area to be fenced** (See Gallagher Energizer Chart page 5)

**3) What power source will you use for your Energizer?**

Gallagher 110 volt Energizers are the best and most economical choice for areas where you have reliable power. Solar/Battery or Solar powered Energizers are the most logical for remote areas.

**4) Do you need a permanent, temporary or offset fence?**

- **Permanent:** Long life, permanent electric fences for highly effective animal control that lasts a lifetime.
- **Temporary:** Easy to transport, assemble and take down allowing flexible fencing for short-term animal control or rotational grazing.
- **Offset:** Protect and extend the life of an existing conventional non-electric fence by adding electric wire(s).

## 2 Year Warranty on All Energizers

All Gallagher Energizers carry a 2 year warranty\* (including lightning damage), in addition to a 30-day money back customer satisfaction guarantee.

\* With Gallagher lightning protection

# Energizer Selection Chart 5

	ENERGIZER	STORED JOULES	'UP TO' DISTANCE CLEAN FENCE (MILES/ACRES)	RECOMMENDED DISTANCE TYPICAL FENCE (MILES/ACRES)	LIVESTOCK CONTROLLED
110 VOLT	M10000i	100.0	1,000 / 6,000	125 / 3,000	
	M5800i	58.0	430 / 2,700	87 / 2,200	
	M2800i	28.0	250 / 1,500	50 / 1,000	
	M1800i	18.0	200 / 1,200	42 / 420	
	M1200i	12.0	120 / 700	37 / 300	
	M1000	10.0	100 / 600	34 / 250	
	M600	6.0	80 / 450	25 / 150	
	M300	3.0	50 / 200	17 / 85	
	M160	1.6	30 / 100	11 / 60	
	M120	1.2	15 / 60	6 / 30	
	M60	0.6	10 / 40	3 / 20	
	M30	0.3	5 / 20	2 / 10	
	M10	0.1	2 / 10	0.5 / 3	
BATTERY	B60	0.6	15 / 60	5 / 40	
	B11	0.11	4 / 20	0.6 / 6	
	B10	0.1	4 / 20	0.6 / 6	
SOLAR/BATTERY	B1600	16.0	180 / 1,000	40 / 400	
	B700	7.0	80 / 450	25 / 200	
	B280	2.8	50 / 200	22 / 110	
	B300	2.6	50 / 200	22 / 110	
	B180	1.8	30 / 100	15 / 90	
	B200	1.45	30 / 100	15 / 90	
	B100	0.8	20 / 70	7 / 60	
	B80	0.8	20 / 70	7 / 60	
SOLAR	S100	1.0	30 / 100	8 / 60	
	S40	0.4	25 / 80	5 / 30	
	S22	0.22	12 / 40	2 / 15	
	S20	0.20	12 / 40	2 / 14	
	S16	0.16	10 / 30	1 / 10	
	S10	0.1	3 / 15	0.5 / 5	

Table is a guide only.

# 6 110 Volt Energizers

## A 110V Energizer System is the best choice if you have reliable power.

All Gallagher 110V Energizers have built in lightning protection and are tested under extreme conditions to ensure unbeatable reliability – delivering outstanding performance day in and day out. Our medium and large Energizers offer extra performance with low power usage by automatically matching power output to fence load, as well as fence monitoring technology giving you total peace of mind your fence is working effectively.

### M10000i

G379514

**100**  
JOULES

*The world's largest, most powerful Energizer.*

- Clean fence distance: 1,000 miles / 6,000 acres
- Typical fence distance: 125 miles / 3,000 acres
- Stored energy (joules): 100

**i Series Energizer System - the fence that can't keep a secret.** Working together the i Series system provides fence information at a glance and if it detects any faults, leads you directly to them, saving you hours of searching.



*A watchful eye on all corners of your fence!  
Add up to six monitors to your fence system.*

Energizer Remote & Fault Finder with user replaceable battery.

Fence Monitors placed strategically around your property provide confident animal control & accelerated fence troubleshooting.



Energizer Controller allows fence information to be seen in a convenient location up to 160' away from the Energizer.

Energy efficient Energizers, adjust power output to suit your fence conditions. Provides incredible fence performance for the unit's size.

#### INCLUDED



#### OPTIONAL ACCESSORIES



## PRODUCTS IN DETAIL:

## FENCE MONITOR



G51000

Sold separately

## A watchful eye on all corners of your fence ↓

Add up to six monitors to your fence system to turn it into a fully monitored set up that keeps the Energizer Controller constantly up to date with fence performance.

- Use across your property to monitor fence voltage and current at up to six different locations (zones)
- Identifies when any zone has a fault and reports back alarms
- Locate fault zones quickly and use the Remote/Fault Finder to pinpoint the problem.

## ENERGIZER CONTROLLER



(Not sold separately, included with M10000i, M5800i, M2800i, M1800i, M1200i)

## Ground breaking innovation, total peace of mind that your fence is working as it should ↓

Shows all your fence performance information (e.g. voltage, faults and location) in one convenient, separate display box that can be placed up to 160' away from the Energizer itself.

- Displays voltage & current readings at the Energizer and for up to 6 attached Fence Monitors
- Locate in a convenient spot for instant updates eg: side of the shed
- Locate fault zones quickly & use the Controller to turn the Energizer on/off
- Fully waterproof for indoor or outdoor placement.

## REMOTE



G50700

Sold separately

## Save hours searching for &amp; fixing faults ↓

The Remote pinpoints the fault within the monitored zone and enables you to turn off the Energizer during repair and on again once complete.

- Shows fence voltages and current
- Shows Alarm status for the Energizer and the Fence Monitors
- One Remote can be used on up to 9 Energizers or use multiple Remotes on one (or more) Energizers.

## Alarm System ↓

Monitor a section of fence and drive external strobe lights, sirens or alarm panels if the circuit is broken eg: gate opened or a wire cut.




Light G56901

Siren G56902



G57900

## IN ACTION:



Fence Monitor(s) recognize any significant drop in fence zone or Energizer performance and raise alarms.



Alerts are sent to the Energizer Controller and/or optional Alarm System.



The Controller and Remote indicate which zone is in fault. The Remote is used to find the fault within the zone.



Power to the fence at the fault location is turned off using the Remote, allowing a safe and convenient repair.



Once the fault is repaired, power is restored to the fence and tested using the Remote.

# 8 110 Volt Energizers

## M5800i

G308514

**58**  
JOULES

- Clean fence distance: 430 miles / 2,700 acres
- Typical fence distance: 87 miles / 2,200 acres
- Stored energy (joules): 58

### INCLUDED



### OPTIONAL ACCESSORIES



## M2800i

G306504

**28**  
JOULES

- Clean fence distance: 250 miles / 1,500 acres
- Typical fence distance: 50 miles / 1,000 acres
- Stored energy (joules): 28
- UL Approved

### INCLUDED



### OPTIONAL ACCESSORIES



### Reliable & adaptive performance even in extreme conditions



- Consistent fence performance regardless of extreme temperature conditions or unreliable power supply
- Peace of mind assured with quick scan LED fence performance lights: green = fence ok, red light flashing = fence fault and solid red light = increased fence load
- User safety and reliable animal control with built in lightning and short circuit protection
- Better fence management with output, ground and fence voltage alarms



## M1800i

G304504

# 18

JOULES

- Clean fence distance: 200 miles / 1,200 acres
- Typical fence distance: 42 miles / 420 acres
- Stored energy (joules): 18
- UL Approved



### INCLUDED



### OPTIONAL ACCESSORIES



## M1200i

G303504

# 12

JOULES

- Clean fence distance: 120 miles / 700 acres
- Typical fence distance: 37 miles / 300 acres
- Stored energy (joules): 12
- UL Approved



### INCLUDED



### OPTIONAL ACCESSORIES



# 10 110 Volt Energizers

## M1000

G382504

**10**  
JOULES

- Clean fence distance: 100 miles / 600 acres
- Typical fence distance: 34 miles / 250 acres
- Stored energy (joules): 10
- Dimensions: 9.6" (w) × 7.5" (h)
- Quickscan Output Voltage: shows output voltage of the Energizer at a glance and a digital output reading
- Ideally suited for large pastures
- UL Approved

LCD voltage and ground displays, provide quick reference to the grounding quality and fence performance.


Quick scan voltage bar graph shows how Energizer is performing at a glance.

Output alarm for better fence management.

Easy to service, modular design.

Green LED indicates normal operation.

Split bolt terminals for easy installation and good connection.



**Terminals connect to:**  
Green - Ground  
Red - Lead out Cable and Fence

### Grazing Management Tips

- Implementing a rotational grazing system allows producers to be more involved in the effectiveness of their forage and how efficiently their cattle graze.
- Cattle must be trained to electric fencing prior to turnout. Temporary fencing is a cost-effective solution to ensure the animals are ready.
- A simple equation to use to determine the number of paddocks to create: number of days of pasture rest divided by the number of days of grazing, plus one.

## M600

G381504

6

JOULES



- Clean fence distance: 80 miles / 450 acres
- Typical fence distance: 25 miles / 150 acres
- Stored energy (joules) : 6
- Dimensions: 9.6" (w) × 7.5" (h)
- Quickscan Output Voltage bar graph: shows output voltage of the Energizer at a glance
- Ideally suited for medium pastures
- UL Approved

## M300

G380504

3

JOULES

- Clean fence distance: 50 miles / 200 acres
- Typical fence distance: 17 miles / 85 acres
- Stored energy (joules) : 3
- Dimensions: 8" (w) × 7" (h)
- Quickscan Output Voltage bar graph: shows output voltage of the Energizer at a glance
- Ideally suited for small pastures
- UL Approved



Green LED indicates normal operation.

Quick scan voltage bar graph shows Energizer performance at a glance.

Split bolt terminals for easy installation and good connection.

## Training Livestock with Electric Fencing

All animals need time and space to discover that electrified fences are hot. This education period must occur under conditions of minimum stress. Select a small, well fenced holding pasture and place offset wires on the perimeter about two thirds the height (nose high) of the animals to be trained.

Ground the remainder of the fence to the Energizer ground and electrify the offset wires with the strongest possible pulse to help make the education process more effective.

If necessary, the remainder of the property can be disconnected to ensure the strongest possible shock during the training period.

Training time: the minimum time required is 12 hours and most animals will be fully trained in 48 hours. The aim is to have stock approaching the fences with caution.

Stock trained to electric fence systems will still respect the fence even if it is off for any reason (we do not recommend turning off an electric fence). Animals that have grown up with electric fence systems have remained in paddocks with the power off for several weeks. In recent years, many graziers have found electric fencing a highly efficient and low cost method of controlling unwanted wildlife.



# 12 110 Volt Energizers

## M160

G330444

**1.6**  
JOULES

- Clean fence distance: 30 miles / 100 acres
- Typical fence distance: 11 miles / 60 acres
- Stored energy (joules) : 1.6
- Dimensions: 9.6" (w) × 7.5" (h)
- Green indicator light flashes when Energizer is working properly
- UL Approved



Power on indicator

Ground terminal

Fence terminal



## M120

G330434

**1.2**  
JOULES

- Clean fence distance: 15 miles / 60 acres
- Typical fence distance: 6 miles / 30 acres
- Stored energy (joules) : 1.2
- Dimensions: 9.6" (w) × 7.5" (h)
- Green indicator light flashes when Energizer is working properly
- UL Approved



## M60

G383414

**0.6**  
JOULES

- Clean fence distance: 10 miles / 40 acres
- Typical fence distance: 3 miles / 20 acres
- Stored energy (joules) : 0.6
- Dimensions: 9.6" (w) × 7.5" (h)
- Green indicator light flashes when Energizer is working properly
- UL Approved





We've taken everything we love about our Energizers and hit the refresh button. The result? Extended mileage with the same unbeatable quality.

## M30

G331434

**0.3**  
JOULES

- Clean fence distance: 5 miles / 20 acres
- Typical fence distance: 2 miles / 10 acres
- Stored energy (joules) : 0.3
- Dimensions: 9.6" (w) × 7.5" (h)
- Green indicator light flashes when Energizer is working properly
- UL Approved



## M10

G331424

**0.1**  
JOULES

- Clean fence distance: 2 miles / 10 acres
- Typical fence distance: .5 miles / 3 acres
- Stored energy (joules) : 0.1
- Dimensions: 9.6" (w) × 7.5" (h)
- Green indicator light flashes when Energizer is working properly
- UL Approved



# 14 Battery Energizers

## A Battery Powered Energizer System needs a constant current.

If not recharged, the battery will eventually become completely discharged and the Energizer will stop. The amount of current required by an Energizer increases with the size of the Energizer. The amount of charge stored by the battery is measured in Amp-hours (Ah) and increases with the size of the battery. A battery should be chosen which is designed for regular charge and discharge cycles, and for discharging most of its capacity without damage.

Deep cycle batteries are recommended as they are the best compromise between price and life expectancy. A deep cycle battery will typically last two to four times longer than an automotive battery when used for powering Energizers because they are designed to be drained and recharged repeatedly.

Batteries should be placed on a level surface and can be protected against extremes of temperature. They should not be in direct contact with a cold surface such as the ground. Placing suitable insulating material under the batteries or placing them in a battery box and burying the box will also help increase their service life. Ensure that the battery has adequate ventilation to allow gases to escape.

### B60

G351504

**0.6**  
JOULES



- Clean fence distance: 15 miles / 60 acres
  - Typical fence distance: 5 miles / 40 acres
  - Stored energy (joules): 0.6
  - Dimensions: 8" (w) x 6" (h)
- Use with a 12-volt, deep cycle battery

### B11

G353414

**0.11**  
JOULES



- Clean fence distance: 4 miles / 20 acres
- Typical fence distance: 0.6 miles / 6 acres
- Stored energy (joules): 0.11
- Dimensions: 4.5" (w) x 8.6" (h)

**Requires:** Six 'D' batteries or external 12V battery (batteries not included). 12V battery leads included.

### B10

G36311

**0.08**  
JOULES

- Clean fence distance: 4 miles / 20 acres
  - Typical fence distance: 0.6 miles / 6 acres
  - Stored energy (joules): 0.08
  - Dimensions: 3" (w) x 6" (h)
- Ideal for protecting gardens from animals.



**Requires:** Six 'D' batteries or external 12V battery (not included). 12V battery leads not included. 12V leads (G52100).

## Sold on Gallagher

Marian Ducrest | Broussard, LA


Until I purchased your B10 Energizer, I'd spend weeks tending my vegetable garden only to have the squirrels, raccoons and rabbits lay waste to it before I could bring in a harvest. I'd tried every deterrent recommended in gardening books and journals only to be consistently frustrated when all my hard work put very little food into my freezer. Your B10 has put an end to that frustration. Since putting it into use I have not lost a single fruit or vegetable to the wildlife.

My garden is approximately 50'x50'. My fence consists of 3 strands of Poly Wire, 1 wire at 4 inches, the second at 8 inches, the third at 20 inches, powered by one B10 Energizer. Most of the time I just step over the fence to get into the garden, but when I need to bring in a tiller, interrupting the power is simplicity itself.

See page 35 for Garden & Backyard Protection Kit.



## A Battery/Solar Energizer System is a popular choice for those without reliable mains power. These Energizers may be operated with or without a solar panel.




### A full Gallagher solar kit set includes:

- High quality fully tested Solar Panels
- A Regulator to protect the battery by controlling the power flow
- Stainless steel Mounting Brackets, Bolts & Clamps for longer life with multiple tilt positions for maximum sunlight exposure

### Solar Panels

Watt Power Output  
(for charging a 12 volt battery)



## B1600

G39600

**16**  
JOULES

- Clean fence distance: 180 miles / 1,000 acres
- Typical fence distance: 40 miles / 400 acres
- Stored energy (joules): 16
- Dimensions: 8.6" (w) x 8.3" (h)
- For remote areas with charging facilities
- Compatible with 90 watt panel
- Complies to RFI (Radio Frequency Interference) standards and has built-in lightning protection circuitry
- Battery consumption, 1,200 milliamps on high power mode and 300 milliamps on maximum save mode
- May be ordered as a solar package (AFR1600)

Quick glance green light shows battery is ok. Flashes red if battery is running low and Energizer slows to half speed to conserve energy.

Flexibility in fence management - choose high, medium or low power operating modes. Also includes low and full output power terminals to operate independently on different fences.



Red light flashes intermittently or not at all if fence is overloaded.

Terminals connect to:  
Green - Ground  
Yellow - Low Power  
Red - Fence Output

Uses a 12-Volt deep cycle rechargeable, marine-type battery. Battery not included.  
Use with 90W Solar Panel A80

# 16 Solar/Battery Energizers

## B700

G39500

**7**  
JOULES

- Clean fence distance: 80 miles / 450 acres
- Typical fence distance: 25 miles / 200 acres
- Stored energy (joules): 7
- Dimensions: 8.6" (w) × 7.9" (h)
- One fully charged 12 volt 100 amp hour battery will operate for approximately 8 days on high power, 14 days on low power
- Compatible with a 40W Solar Panel
- May be ordered as a Solar Package (AFR700)

Flashing red light shows when battery is low and Energizer slows to half speed to conserve energy.



Neon fence light flashes intermittently or not at all if fence is overloaded.

Uses a 12- Volt deep cycle rechargeable, marine-type battery. Battery not included.

Switch to select high or low power.

## B280

G366504

**2.8**  
JOULES

- Clean fence distance: 50 miles / 200 acres
- Typical fence distance: 22 miles / 110 acres
- Stored energy (joules) : 2.8
- Dimensions: 8" (w) × 6" (h)
- Built in battery-save feature extends battery life.
- Easy to use 5-stage rotary dial to change Energizer operating functions.
- May be ordered as a Solar Unit (AFR280)
- Convert to 110v (G40101) optional

Rotary dial to change Energizer operating functions.

- Battery Check
- Off
- Full Power

Battery save modes

Half power

Night save 1.8x more battery life

Quick glance indicator light shows battery and fence voltage performance.



Split bolt recessed terminals for easy installation and good connection.

## B300

G394SK

**2.6**  
JOULES

- Clean fence distance: 50 miles / 200 acres
- Typical fence distance: 22 miles / 110 acres
- Output energy (joules): 2
- Dimensions: 12.6" (w) × 15" (h)
- Highly visible low-battery and fence-voltage indicator lights
- Carrying handle for easy transportation
- Weatherproof enclosure to contain battery
- May be ordered as a battery only unit (G39400)
- Replacement fence and ground leads (G57300)
- Unit has a hole in the bottom enabling it to be staked to prevent theft

Shown here with solar panel.  
Please ask about our battery only option.

Uses a 12- Volt deep cycle rechargeable,  
marine-type battery. Battery not included.

## B200

G393SK

**1.45**  
JOULES

- Clean fence distance: 30 miles / 100 acres
- Typical fence distance: 15 miles / 90 acres
- Stored energy (joules): 1.45
- Dimensions: 12.6" (w) × 15" (h)
- Highly visible low-battery and fence-voltage indicator lights
- Carrying handle for easy transportation
- Weatherproof enclosure to contain battery
- May be ordered as a battery only unit (G393454)
- Replacement fence and ground leads (G57300)
- Unit has a hole in the bottom enabling it to be staked to prevent theft

Quick glance indicator lights  
show battery and fence  
performance.

Versatile animal control -  
vary Energizer pulse modes  
to suit different animals.

Flexible fence management  
- choose from full or half  
power mode to extend  
battery life.

Carry handle for easy  
transportation.

## B100

G392SK

**0.8**  
JOULES


- Clean wire distance: 20 miles / 70 acres
- Typical fence distance: 7 miles / 60 acres
- Stored energy (joules): 0.8
- Dimensions: 12.6" (w) × 15" (h)
- Highly visible low-battery and fence-voltage indicator lights
- Carrying handle for easy transportation
- Weatherproof enclosure to contain battery
- May be ordered as a battery unit (G392454)
- Replacement fence and ground leads (G57300)
- Unit has a hole in the bottom enabling it to be staked to prevent theft

Easy battery  
installation,  
with simple clip  
lock case.





# 18 Solar/Battery Energizers



## 80 Miles of Gallagher Electric Fencing Does the Job Right

### B180

G364504

**1.8**  
JOULES



- Clean fence distance: 30 miles / 100 acres
- Typical fence distance: 15 miles / 90 acres
- Stored energy (joules): 1.8
- Dimensions: 8" (w) x 6" (h)
- Built in battery-save feature extends battery life.
- Easy to use 5-stage rotary dial to change Energizer operating functions.
- Compatible with 10 Watt Solar Panel
- Order as Solar Unit (AFR180)
- Convert to 110V (G40401)

### B80

G362504

**0.8**  
JOULES



- Clean fence distance: 20 miles / 70 acres
- Typical fence distance: 8 miles / 55 acres
- Stored energy (joules): 0.8
- Dimensions: 8" (w) x 6" (h)
- Built in battery-save feature extends battery life.
- Easy to use 3-stage rotary dial to change Energizer operating functions.
- Compatible with 10 Watt Solar
- Convert to 110V (G40401)
- Optional solar package (AFR80)

Doak Elledge makes good use of electric fencing on the 11,000 acre Faudree Ranch, near Pampa, TX. The ranch is made up of 60 permanent pastures, varying from 15-680 acres. About 175 acres of improved pasture is subdivided with temporary fencing using Gallagher Tumblewheels and reels with Poly Tape.

"We have been using electric fencing since 1982," says Elledge. "We use 2 and 3 wire fence on permanent divisions and signal wire with temporary fencing. We run one herd of 450-500 cows in the summer and we pasture another, 850-900 yearlings."

*"The main reasons we went to electric fencing were the lower costs and the maintenance efficiencies. We can construct approximately 4-5 miles of electric fence at about the same cost for 1 mile of barbed wire fence."*

For new cattle, Elledge uses training traps with 4 and 5 wire electric fence. "Usually, after 1-2 days the cattle leave the fences alone," explains Elledge. "Most of the fence with the cow herd is 2 wire. The bottom wire is ground and the top wire is hot. This way, when the calves are young they can cross back and forth."

"We are constructing many of our fences with Gallagher Fiberglass posts," says Elledge. "So far, we really like this new type of fence. There are a lot of new products for electric fencing and they offer real advantages over the old style of construction, but even at that some of our 10 year old electric fences are still holding up well."

Are you looking for an Energizer that generates free energy and is environmentally friendly? Go solar. Check out our full line up of high quality, reliable solar systems that are a cinch to install and will last for years.

## S100

G346404

**1.0**  
JOULES

Multiple power options - Wildlife mode pulses fast day and night. Full power mode pulses fast during the day and slower at night, conserving power when animals are less active.

- Clean fence distance: 30 miles / 100 acres
- Typical fence distance: 8 miles / 60 acres
- Stored energy (joules) : 1
- Dimensions: 12" (w) x 12" (h)
- Safe, powerful animal control designed for outdoor and portable use
- Can be mounted on a wall, wood post, or T-Post
- Highly visible rotary dial for turning the unit off and on
- Impact resistant plastic lens to protect the solar panel
- Easy to maintain and clean
- Maintenance-free rechargeable battery and leads included



Turn on and forget - With automated battery management, energizer will continue to work for up to 3 weeks without sun.

Indicator light for fence power

Water resistant case, with built in lightning protection - designed to be left outside, rain, hail or shine. Keeps stock contained in all weather conditions.

Quick to install - Easily set up and portable for grazing and better pasture management.

**S100 RECHARGEABLE BATTERY**  
A738  
Used in the Gallagher S100 Energizer.

## S40

G359404

**0.4**  
JOULES

- Clean fence distance: 25 miles / 80 acres
- Typical fence distance: 5 miles / 30 acres
- Stored energy (joules) : 0.4
- Dimensions: 12" (w) x 12" (h)
- Safe, powerful animal control designed for outdoor and portable use
- Can be mounted on a wall, wood post, or T-Post
- Highly visible rotary dial for turning the unit off and on
- Impact resistant plastic lens to protect the solar panel
- Easy to maintain and clean
- Maintenance-free rechargeable battery and leads included



**S40 RECHARGEABLE BATTERY**  
A0959  
Used in the Gallagher S40 Energizer.

# 20 Solar Energizers

## S22

G344414

**0.22**  
JOULES

- Clean fence distance: 12 miles / 40 acres
- Typical fence distance: 2 miles / 15 acres
- Stored energy (joules) : 0.22
- Dimensions: 11.6" (w) × 12" (h)
- Large terminals enable correct grounding for best Energizer performance
- High-impact, UV-resistant plastic case for weatherproof, rust-proof, insect-proof outdoor use
- Maintenance-free rechargeable battery included
- Fits on top of steel t-post
- Automatic night save mode to extend battery life
- Battery & leads included

Built in solar panel charges battery for consistent, reliable fence performance.

**S22 RECHARGEABLE BATTERY 6V A670**  
Used in the Gallagher S17 & S22 Energizer.

Fence and ground leads (G59300).



## S20

G341424

**0.20**  
JOULES

- Clean fence distance: 12 miles / 40 acres
- Typical fence distance: 2 mile / 14 acres
- Stored energy (joules) : 0.20
- Dimensions: 9" (w) × 10.5" (h)
- Large terminals enable correct grounding for best Energizer performance
- High-impact, UV-resistant plastic case for weatherproof, rust-proof, insect-proof outdoor use
- Maintenance-free rechargeable battery included
- Fits on top of steel t-post
- Unique battery save extends usage up to 3 weeks without sun
- Automatic night save mode to extend battery life
- Battery and leads included

**S10/S16/S20 RECHARGEABLE BATTERY 6V A905**  
Used in the Gallagher S10/S16/S20 Energizers.





# S16

G341414

**0.16**  
JOULES

*Operates up to 3 weeks without sun!*

- Clean fence distance: 10 miles /30 acres
- Typical fence distance: 1 mile / 10 acres
- Stored energy (joules) : 0.16
- Dimensions: 11.6" (w) × 12" (h)
- Large terminals enable correct grounding for best Energizer performance
- High-impact, UV-resistant plastic case for weatherproof, rust-proof, insect-proof outdoor use
- Maintenance-free rechargeable battery included
- Fits on top of steel t-post
- Unique battery save extends usage up to 3 weeks without sun
- Ideal for managed grazing, this robust and portable unit makes a great alternative to battery powered systems



360 Degree T-Post mount allows the Energizer to mount onto existing posts.

Built in solar panel (1.5 Watt) charges battery for consistent, reliable fence performance.



Battery light indicator

Water resistant case & components with built-in lightning protection. Designed to be left outside in all weather conditions.

Fence and ground leads (G59300).

**S10/S16/S20 RECHARGEABLE BATTERY 6V A905**  
Used in the Gallagher S10/S16/S20 Energizers.

# S10

G341404

**0.1**  
JOULES

*Operates up to 3 weeks without sun!*

- Clean fence distance: 3 miles / 15 acres
- Typical fence distance: 0.5 miles / 5 acres
- Stored energy (joules) : 0.1
- Dimensions: 9" (w) × 10.5" (h)
- The Energizer comes with a battery and solar panel. Leads are not included
- Unique battery save extends usage up to 3 weeks without sun
- Built in lightning protection
- Designed for all weather conditions



360 Degree T-Post mount allows the Energizer to mount onto existing posts.



Fence and ground leads (G59300).

**S10/S16/S20 RECHARGEABLE BATTERY 6V A905**  
Used in the Gallagher S10/S16/S20 Energizers.


# 22 Grounding

## Eight out of ten problems are due to improper grounding

Setting up a good grounding system is often overlooked but it's critical. It's how the power flows from the Energizer, to the fence, through the animal and back through the ground to the Energizer. Without good clean ground rods in sufficient size and number the ground connection doesn't work and the shock will not reach the animal.


### For Wetter Regions

For use in greener regions where the fence can be simplified to an 'all live wire' system.



### For Drier Regions

For use where the ground struggles to conduct enough power. A 'ground return system' is created where the live & ground wires on the fence create the shock when the animal touches them both at the same time.



### Handy Hint


The rule for ground stakes when installing permanent fencing

- 10' Between ground rods
- 3 Ground rods minimum\*

- 6' Minimum length of rods
- 1 Wire connecting all rods to Energizer ground terminal

As a rule of thumb, use at least 3 ground rods or the Energizer Stored Joules rating divided by 5.

### GROUNDING



Recommended grounding option; equivalent to **three** ground rods. Particularly effective in poor grounding soils.

**6' Ground Rod**  
A351

**3' Ground Rod**  
A351A

**HD Ground Rod Clamp**  
A352HD

**HD Ground Rod Clamp (3 pk)**  
A363HD

**Complete 3-Ground Rod Kit**  
A655

- Three 6' galvanized rods
- Heavy-duty clamps
- 50' of 12 gauge galvanized wire

**Super Grounding Kit**  
G88000

- One stainless steel rod
- One galvanized ground clamp
- 13.5 lbs of absorbent mixture
- The equivalent to using three 6' ground rods



## FENCE TESTERS

### Fence Volt/Current Meter and Fault Finder G50905

#### Save hours searching for and fixing faults

- Large easy to read LCD display shows voltage & current
- Large arrows show direction of fault
- Auto On/Off when fence pulse detected



### Energizer Remote and Fault Finder G50700

Quickly and easily locates fence faults. Once fault located turn the Energizer off remotely to allow safe and convenient fence repair. Rugged and reliable with a tough, water resistant casing.

Compatible with M10000i, M5800i, M1800i & M2800i



### Fence Volt Meter G503014



Digital read out for accurate fence voltage measurement.

### Fence Volt Indicator G501004



Simple indicator lights show approximate fence voltage levels.

## FENCE MANAGEMENT TOOLS

### Live Fence Indicator G51100

#### Know your fence is working!

Place permanently on your fence and simply look for the LED flash, for instant reassurance that the fence is working.

- No batteries required. Uses power from the fence (2kv or 2000 volts or higher)
- Highly visible LED can be seen during day/night (up to .5 mile at night)
- Long life - water and UV resistant
- Simply put ground rod in and clip on to fence wire or tape.



### Cut Out Switch G60731

A handy tool that allows a section of a permanent fence to be switched off for maintenance or fault finding.

- High quality phosphorous bronze contacts for long life & maximum effectiveness
- Highly visible on/off switch for status checking at a glance
- Full sealed, weatherproof & dirt resistant.



### Knife Cut Out Switch G610



Alternative cut out switch option.

- Stainless steel contacts
- Easy to see open or closed status
- Use at gates and for easy location of fault finding
- Switch off a section of fence for maintenance and routine checks

## SAFETY & PROTECTION

### Flood Gate Controller G60400



Install on flood gates to prevent significant power loss when the water way is flooded.

### Voltage Spike Protector A209



Protect your fence from damaging power surges.

### Lightning Diverter G64800

Also available porcelain (A207)



Gallagher recommends that all Energizers be fitted with a lightning diverter to help protect from lightning damage. This diverter will withstand multiple lightning strikes and can be adjusted to fit any Energizer.

### Warning Sign G602404



A highly visible sign that warns that a fence is electrified. Required by law, to be used on boundaries and anywhere else public have access to a fence.



# 24 Strainers, End Strain Insulators



**GROUND BREAKING  
UV RESISTANT MATERIAL**  
Improves insulator life by  
maintaining flexibility on the fence



STRENGTH



10 YEARS WARRANTY



## END STRAIN INSULATORS AND STRAINERS

**Strain Insulator**  
White: G67812  
Black: G67702



Strongest, long term end strain insulation for high tensile permanent electric fencing.



**In Line Wire Tightener**  
G64304  
G64302 - 5 Pack



Fits over wire for mid-fence straining, increasing effectiveness of strain by pulling from both directions. Ideal for tightening existing fences or trellising wires.



**Strain Insulator Kit**  
G61814



Simplest option for end strain insulation; comes with pre-attached wire rope. Fits up to 7.5" posts. No wire tying or special tools needed.



**Porcelain Round Insulator**  
G674034



Fire resistant, high quality glaze finish porcelain doughnut is 1.5" in diameter.



**Insulated Wire Strainer Kit**  
G618034



No wire tying, fast & simple. Includes all three end strain elements - insulator, strainer and steel rope. Simply slide over the post and you're done. Fits up to 7.5" post.



**Porcelain High Strain Insulator**  
G692034



This long-life, fire resistant insulator is suitable for long strains of permanent fence.



**Insulated Wire Strainer**  
G79553



Combined end strain insulator and strainer. Simply tie onto strainer post and wind fence wire onto spool. Tighten with G69530 ratchet handle.



**Screw-In Tie Down & Handle**  
G61500 Tie Down  
G615014 Handle



Ensures a secure fence tie down. Tie down and handle sold separately.



**Insulated Strainer**  
G74313



Insulated body provides 1.7 x the insulation of previous models.



**Insulated Tube**  
G614134 - White  
G614034 - Black



23" Long protective strips for poly wire or braid. Available in white 82' coil.



**Insulated Tube**  
A213



100' coil. Alternative to longer life, higher strength insulators.



**Wire Strainer**  
G79504



Ratchet style wire strainer. Can also be used in-line by threading through strainer. Tighten with G69530 ratchet handle.



**End/Corner Tensioner**  
AH125



Firmly secures 1.5" tape. The unique clasp on this impact resistant polyethylene prevents movement and helps eliminate wear.

**HD Tension Spring**  
A290



A versatile product with in-built over-stretch protection. Use for:

- Fences with frequent snow loads
- Enabling irrigators to pass over fence lines
- On very short fence lines to maintain tension and prevent excessive strain on end posts.



**Tape End Tensioner**  
AH120




**Tape Joiner 1.5"**  
AH105



Used to join 1.5" tape. This stainless steel material is rust resistant.





## WOOD POST INSULATORS

**Wood Post Claw Insulator**  
G67304



The most popular choice for permanent electric fencing using wood posts.



**Wood Post Pinlock Insulator**  
G68704 - Black  
G687144 - White



Used with high-tensile wire.



**Wood Post Screw-in Ring Insulator**  
G66604 - Black  
G667 - White



Angled slot allows quick securing and safe holding of wire. No need to create pilot hole first, simply screw into soft wood.



**Wood Post Wide Jaw Claw Insulator**  
G67614 - White  
G676044 - Black



Specifically for Equine Fence Wire, the most popular choice for permanent equine fencing using wood posts.



**Wood Post Wide Jaw Pinlock Insulator**  
G626144 - White  
G626044 - Black



Extra-large shield eliminates power leakage through tracking. Accommodates Equine Fence and braid products.



**Wood Post Heavy Duty Tape Insulator**  
G66913 - White  
G669034 - Black



Soft rubber jaws lock 1.5" tape in place and prevent wear. Unique rubber pad eliminates tape wear.



**Wood Post Corner Strain Tape Insulator**



G670034 - Black w/steel plate

## WOOD POST INSULATORS

**Corner Lag Insulator**  
G679 - White  
G688 - Black



This polycarbonate insulator with UV and color preservation is great for pulling through corners.



**Large Porcelain Lag Insulator**  
G675



Long-life, fire resistant porcelain.



**Standard Porcelain Lag Insulator**  
G671



Long-life, fire resistant porcelain.



**Wood Post Tape Insulator**  
G668144 - White  
G668044 - Black



Designed specifically for Poly Tape up to 1.5" wide. Staples to post and clamps to fiberglass.




SEE MULTI-PURPOSE INSULATOR ON PAGE 26

## CLAMPS

Two options for clamping multiple HT wires in a secure electrical connection. Dedicated option for thicker wire/cable.

**Joint Clamp L Shape**



Wing nut:  
G603934 - 10 pk

**Joint Clamp Hexagonal**  
G603534 - 10 pk  
G60355 - 25 pk



Hex nut:  
G603034 - 10 pk  
G603044 - 25 pk



## WIRE CONNECTOR

**Split Bolt Wire Connector**  
G605 - 5 pk



Connects high tensile or regular wire with jumper or lead-in wire.

Ensures good electrical connections.




**Equine Fence Joiner**  
AH101



Join Equine Fence or 12.5 gauge wire without special tools or crimps. Simply strip special polymer coating off Equine Fence and insert bare wire into joiner.



# 26 Steel & Fiberglass Post Insulators



Steel Post Insulators

## T-POST INSULATOR S

**T-Post Wide Jaw Pinlock Insulator**  
G682134 - White  
G682034 - Black



Fits all T-Posts from 1.25" to 1.5". This unique snap on design requires no tools to install. The wide jaw accommodates Equine Fence and braid products.



**T-Post Tape Insulator 1.5"**  
G654134 - White  
G654024 - Black



Fits all T-Posts from 1.25" to 1.5". No tools are required to install. Specifically designed for .5"-1.5" tape. Will accommodate Equine Fence and braided products.



**T-Post Topper Insulator**  
G685134 - White  
G685024 - Black



Safety and flexibility - add a single electric wire/tape/braid to the top of existing posts using this protective cap. Top accommodates .375" wire. Front accommodates 1.5" tape and .375" wire.



## IN LINE FIBERGLASS & ROD POST INSULATORS

**Spring Grip Post Clip**  
A636



Clip for secure attachment to .375" fiberglass post.



**Rod Post Screw-on Claw Insulator**  
G65514 - White



For round posts for 1/4" - 5/8" diameter.



**Rod Post Screw-on Claw Insulator 3/8"**  
G65604 - Black



Claw style insulator for fitting plastic wire to round or oval portable posts with 3/16"-3/8" diameter. Fits Ring Top Post.



STRENGTH



WARRANTY

## MULTI-PURPOSE INSULATOR



**Multi-Post Wide Jaw Pinlock Insulator**

G681134 - White  
G681034 - Black

Heavy Duty, snap-on plastic insulator designed for steel posts, but can be nailed to wooden posts or screwed to vinyl posts.



## STANDARD INSULATOR LINE

**Std T-Post Claw Insulator**  
G73104



Simple snap on design for common T Post sizes.



**Std Wood Post Nail-on Claw Insulator**  
G73604



Single fixing point. Wrap feature for poly wire strength. Comes with nail.



**Std Wood Post Screw-in Ring Insulator**  
G73704



Angled slot for wire retention. Extra insulating of flanges to prevent arching.



**Std Donut Insulator**  
G73503



Glass filled polypropylene construction.



**Std Rod Post Screw-on Insulator**  
G73404



Fits a 3/8" post. Nut comes attached to insulator body to prevent lost parts.



**Std Strain Insulator**  
G73303



Large insulating shields. Approximately 66 lbs. max tension load.





**Std T-Post 5" Claw Offset Insulator**  
G73204



Simple snap on design for common T Post sizes.






## WIRE MOUNTED OFFSETS



### Bracket Offset with Plastic Pinlock Insulator 12"

G665144 - White Replacements  
 G665044 - Black Replacements  
 G659034 - Black, 10 pk  
 G659154 - White, 50 pk  
 G659054 - Black, 50 pk



This offset will attach to any existing wire fence and comes pre-assembled.

Available with Porcelain insulator (G664054). Also, available for wood posts (G662054) and chain link (G653054).




## PIGTAIL & WOOD POST OFFSETS



Popular option for adding an electric wire to existing wood post fences. Use side mount option for standard height or top mount for a higher top wire placement (e.g.: horses) and one or both sides of the post.

### Side Mount Pigtail Offset



**6.5" Side or Top**  
 G660214 - White  
 G610224 - Black



### Side Mount Pigtail Double Offset



**25.5"**  
 G610424 - Black



### Wood Post Pinlock 5" Offset Insulator

G617134 - White  
 G617034 - Black



The pinlock allows for easy fence construction and wire removal. The wide jaw accommodates Equine Fence and braid products.



## Benefits of Offset Fencing

Old fences can be made to last for many more years by simply attaching offset brackets and an electrified wire on one or both sides, even where fences have deteriorated so much that they need replacing.

New fences will last almost twice as long if they have electrified offset wires attached to them. Electrifying one or more wires in a conventional non-electric fence will prevent stock pushing through the fences.

Attach single offset wires at two thirds the animal to be controlled. If sheep and cattle are to be in the same area, use two wires or a single offset attached at three quarters the height of the sheep.

Where old barbed wire is rusty and broken, remove the worst wires and tighten the others to prevent an ongoing problem of them shorting out the offset wire. Old fence wires can also be connected in parallel and used as a ground return.



## T-POST OFFSETS



### T-Post Pinlock Offset Insulator - 5"

G650134 - White  
 G650034 - Black



Extra locking tab enables offset to fit all T-Posts from 1.25" to 1.5". The pinlock allows for easy construction and wire removal. The wide jaw accommodates Equine Fence and braid products.



### Multi-Post Pinlock Offset Insulator

G694134 - White  
 G694034 - Black



This multi-purpose insulator is able to be attached to both sides of a steel post or nailed to a wooden post. It has a pinlock clip that allows for easy fence construction.





## Ensure optimum power to all parts of the fence

Lead out describes the cable and wire that carries the power from the Energizer to the middle of your fence system. Much like your property water system, ensure optimum power distribution to all areas of your fence by choosing the most conductive cable/wire (biggest feeder pipe) relevant to your fence system.

### DOUBLE INSULATED CABLE: Energizer to the fence



**Double Insulated Cable**  
G609024 165'  
16 Gauge



This double insulated cable has a resistance of 160 Ohms/mi.

**High Conductive Cable**  
G62793 330'



This 12.5 gauge aluminium coated cable is ideal for long distances underground, through buildings or where there are numerous gateways in the leadout system. Three times the conductivity of 12.5 gauge galvanized wire.

**Double Insulated Hard Cable**  
G627034 330' Black  
G627014 65' Black  
G627044 65' White



Made of 12.5 gauge steel and is ideal for standard leadouts and undergate cabling.

### ELECTRIC FENCE WIRE: Fence to middle of system



**High-Tensile Wire**  
A303 .5 mile



- Engineered and manufactured especially for permanent fencing. This 12.5 gauge wire is much stronger than standard fence wire and class III galvanized for longer life - 170,000 PSI.

**Aluminium Wire**



AXL17250 17 Gauge; 250'  
AXL171320 17 Gauge; 1320'  
AXL141320 14 Gauge; 1320'  
AXL142640 14 Gauge; 2640'  
AXL121320 12.5 Gauge; 1320'  
AXL124000 12.5 Gauge; 4,000'

- Ideal for long leadout with very high powered Energizers. Never rusts; a permanent solution even in harsh environments. Conducts electricity four times better than steel wire.

Easy to re-spool and ideal for controlled grazing.

1/3 Weight of steel

### WIRE ACCESSORIES:



#### Staples

AC680 1.75" Barbed Staples 10 lb pail  
AC681 2" Barbed Staples 10 lb pail  
AC683 1.5" Barbed Staples 10 lb pail



#### Wire Splicing Sleeves

A800 FW3-4 Wire Splicing Sleeve (10-11 Gauge Smooth)  
A401 FW4-5 Wire Splicing Sleeve (9 Gauge Smooth)  
A802 FW2-3 Wire Splicing Sleeve (12.5 Gauge Smooth)



#### Wire Line Taps

A405 FWT2-3 Line Tap (12.5 Gauge Smooth)  
A811 FWT4-5 Line Tap (12.5 Gauge Barbed)



## Using Insulated & Underground Cable

Leadout Cable or Double Insulated Cable should be used in buildings, under gateways and where soil could corrode exposed galvanized wire.

Undergate cables should not be used for long leadouts or for long distances underground, because the 16 gauge galvanized wire will cause resistance to the flow of the current. This is not so important on small properties, but where long distances of fencing are to be erected use 12.5 gauge Leadout Cable or High Conductive Cable.

Never use household electrical cable; it is made for a maximum of 440 volts and for inside work only.

Never use copper wire undergate cable because electrolysis problems occur where it is joined to galvanized fencing wire.





Conductor Selection Chart			FENCE VOLTAGE			RESISTANCE (Ohms/miles)	MIXED METALS*	
			328' FENCE	1,640' FENCE	3,280' FENCE			
Braid, Wire, Rope	<b>A) Turbo Braid - 3/16"</b> G62174 656', White G62176 1,312', White G621774 1,312', Green		<ul style="list-style-type: none"> <li>9 Mixed metal strands</li> <li>Most user-friendly for horse fencing - visible and safe</li> <li>Best suited for any distance temp or permanent fence</li> </ul>	8kV	7.5kV	7.1kV	125	▪
	<b>B) Turbo Braid - 7/64"</b> G62148 1,312', White/Blue		<ul style="list-style-type: none"> <li>9 Mixed metal strands</li> <li>Superior heavy duty strength</li> </ul>	8kV	7.5kV	7.1kV	125	▪
	<b>C) Turbo Wire</b> G62054 656' G620564 1,312' G62089 2,624'		<ul style="list-style-type: none"> <li>9 Mixed metals</li> <li>Best suited to distances more than 1/4 mile, where extreme power is required</li> <li>40 times more conductive than standard Poly Wire</li> </ul>	8kV	7.5kV	7.1kV	130	▪
	<b>D) Poly Wire</b> G62004 656' G620300 1,640'		<ul style="list-style-type: none"> <li>6 Stainless steel strands</li> <li>Best suited for distances under 1/4 mile</li> </ul>	5kV	2kV	1kV	6,000	
5" Tape	<b>E) 5" Turbo Tape</b> G62354 656' G62356 1,312'		<ul style="list-style-type: none"> <li>Mixed metals 30x's more conductive</li> <li>Best suited for distances greater than 1/4 mile</li> </ul>	7.8kV	7.1kV	6.4kV	250	▪
	<b>F) 5" Poly Tape</b> G62304 656'		<ul style="list-style-type: none"> <li>6 Stainless steel strands for good conductivity</li> </ul>	4.3kV	1.5kV	0.8kV	8,500	
1.5" Tape	<b>G) 1.5" Turbo Tape *</b> G624544 656'		<ul style="list-style-type: none"> <li>15 mixed strands for ultra high conductivity</li> <li>Reinforced edges for longer life &amp; open weave for low wind resistance</li> </ul>	7.8kV	7.1kV	6.4kV	250	▪
	<b>H) 1.5" Poly Tape *</b> G624044 656'		<ul style="list-style-type: none"> <li>15 Stainless steel strands</li> <li>Ideal for portable electric fences</li> </ul>	4.3kV	1.5kV	0.8kV	8,500	
Other	<b>I) Equine Wire *</b> G912064 1,000'		<ul style="list-style-type: none"> <li>Ideal for horse fencing - safe and effective</li> <li>Best for permanent fence - 12.5 g core</li> <li>Med tensile galvanized wire -10 Year warranty</li> </ul>	7.7kV	7.5kV		22	

\* recommended for horses

# 30 Reels

Gallagher has a wide range of reels, portable posts and fence wires to make portable fencing easy and effective. Discover the best choice below to meet your needs.



## GEARED REELS

**Geared Reel**  
G61150 (Note: Reel does not come pre-wound)

**Securely attach to wire or ATV with locking device**

Most popular option for fast winding (2.7:1) on standard length portable fences.

Approx. capacity: .31 mile Poly Wire, .25 mile Turbo Wire or .05 mile Tape.



**Geared Large Reel**  
G63150

Larger capacity for bigger paddocks

Approx. capacity: .74 mile Poly Wire, .62 mile Turbo Wire or .25 mile Tape.



## NON GEARED REELS

Lightweight & strong, for use on shorter, less frequently moved portable fences.

**Standard Reel**  
G61100

Approx. capacity: .31 mile Poly Wire, .25 mile Turbo Wire or .05 mile Tape.



**Economy Reel**  
G61600

.33 mile Poly Wire capacity or .25 mile Turbo Wire capacity.



## REEL ACCESSORIES

**Reel Stand**  
3' 1-3 reels  
G63300



Rust resistant steel, tread-in post for holding up to 3 reels for strip grazing and temporary fencing. Includes chain for securing to a post.

**Wire Guide**  
G61200



Reel guide replacement, for tangle free operation.

**Mini Reel**  
G63030

Ideal for small amounts of Poly Wire (.124), Turbo Wire (.09 mile) or Turbo Braid (.03 mile) such as camp corrals.



## POWER CONNECTORS

UV resistant leads connect a portable fence to a permanent fence.

**Single Reel Lead Connector**  
G634004




## Tumblewheel

G63800

Enables you to quickly and easily roll a fence line to a new position. The Tumblewheel's unique center hub maintains power while the fence is being moved. It can also be used on flat, very hard and frozen ground. The legs remain live except for the two legs that are on the ground.

Where several breaks are needed in one paddock, Tumblewheels are ideal for quick and efficient rationing of grass. This fence consists of a number of electrified 'wheels' spaced across the pasture. Fences up to 660' and is easily managed from one end. 66' spacing of Tumblewheels is achievable on level ground.

The wheels are held upright with the tension of the single line fence which passes through the center. When one or both ends of the fence is moved, the wheels roll along. When you stop, the fence stops.



### POSTS (All heights are from the foot)



Pigtail Standards – the most popular option for dairy & beef cattle

#### Standard Pigtail G64219

Ideal for softer ground, welded foot design reduces tangling.



#### Heavy Duty Pigtail G64245

Ideal for hard ground. 42" (including spike).

Crimped foot to ensure shaft strength.



#### Fiberglass Rod Post A635 - White G81433 - Orange

.375" x 48". Made of highly visible white fiberglass.

Use with A636 Quick Clip.



Multiwire Treadins – multiple lug positions for many animal types

#### Double Foot Treadin G72413

This very sturdy and durable plastic post is 42" high (including spike) with 9 numbered lugs designed for virtually all animal types.



#### Heavy Duty Treadin G636054 White G63655 Orange

UV stabilized plastic treadins with up to 9 lugs for positioning wires and tape.

42" high (including spike)



#### Ring Top Post G72315

### No more tangled posts!

With a head that will not wear through, a super strong foot plate that will not bend under pressure and a sleek design that significantly reduces tangling, the Ring Top Post combines more strength with less frustration. 33" in height.



#### Insulated Line Post

G74213 - 45"  
G74223 - 53"  
G74434 - Bag of 20 Clips

The composite post can be easily installed with a driver reducing installation time and the need for heavy equipment. Wires simply clip onto the post, making it significantly faster than stapling or pinning on traditional post insulator systems.



#### 7/8" Fiberglass Fence Post

Use where a permanent fence post is required. Often used in feedlots or near buildings where animals may be pushed into the fence. These posts are pre-drilled every 2" for convenient wire spacings with exception of bottom 18" on FRP60, FRP66 and FRP72.

25 Year UV protection warranty.

AFRP48 - 48"    AFRP66 - 66"  
AFRP60 - 60"    AFRP72 - 72"



#### Fiberglass Post Clips G70400

Made of galvanized, mild steel. Fast and easy design to use.



#### Fiberglass Stay Clips G70200

Made of galvanized mild steel. The tight tie prevents slipping.






# 32 Gate Kits and Gate Accessories

## How to compare under gate cable


Choosing higher conductive under gate cable will ensure maximum power transfer between the two fence sections. Look for the lowest resistance rating per mile.

Soft cable is easier to strip while hard cable offers the best protection in the ground (note Gallagher recommends cable be installed through pipe for ultimate protection, especially in rocky ground).



### ELECTRIC GATE HANDLES

**Heavy Duty Gate Handle**  
G639304



Flat hook for maximum electrification and extra safe handle which pulls out on impact. Heavy-duty tension spring.

**Gate Handle**  
G691104  
(White)



Large shield on handle to protect from shocks.

**Gate Handle**  
G689404  
(Green)



Highly visible green insulated handle. Large shield on handle to protect from shocks.

**Insulgrip**  
G606304



Insulated hook for quick and secure attachment of portable fences.

**Rubber Grip Gate Handle**  
G69603  
(for Tape)



Premium gate handle with comfortable rubber grip handle, and unique internal overstretch protection.

G69703  
(for Wire)



Wire and tape versions available.

Quick & secure portable fence attachment to permanent electric fence wire. The Dual Purpose Handle option provides flexibility to liven the fence from either the reel or handle end.

**Insulated Handle**  
G73730



**Dual Purpose Handle**  
G73830



### SINGLE STRAND KITS

All Gallagher gate kits include a high visibility flag.

**Electric High Visibility Spring Gate**  
G64010



Highly visible electrified gate with insulated gate handle. Gate width is up to 16.5'.

Kit includes: insulator 3-way gate anchor, gate handle and all metal galvanized and powder coated spring.

**Electric Tape Gate**  
G64100



White 1.5" tape and insulated gate handle for high visibility. Gate width is up to 16.5'. Includes stainless steel tape joiners.

**Electric Bungy Gate**  
G64050



Highly visible shock cord that stretches to 11.5' to 23'.

Kit includes: insulator 3-way gate anchor, gate handle and bungy cord with UV stabilizer.

### GATE ACCESSORIES

**Multi Post 3-Way Gate Anchor**  
G649114



Super strong live anchor for up to three gates coming to a junction. Ideal for use in gateway systems at the intersection of multiple paddocks.

**One-Hand Gate Latch**  
F0202U




Includes two staples and a 14" chain that is easy to attach and can be padlocked. Made from silver zinc passivate material.

GATE ACCESSORIES




**Lock Through-Post Gate Hanger**



This zinc coated locking arm prevents the gate hanger from turning in the post.

	A	B	C	D
<b>F0042U</b>	.625"	1.625"	4"	10"
<b>F0046U</b>	.75"	2"	4"	14"

**Through-Post Gate Hanger**



This zinc coated long pin (B) makes gate hanging easier by allowing the gate to slide down the long pin before engaging a short bottom pin. The long pin can be padlocked.

	A	B	C
<b>F0023U</b>	.625"	1.625"	10"
<b>F0029U</b>	.75"	2.75"	14"

**Standard Strap Hinge**  
F0125U



Zinc coated strap hinge that measures .625" x 12".

**Heavy-Duty Strap Hinge**  
F0132U



Zinc coated strap hinge that measures .75" x 15".

OTHER GATE KIT OPTIONS



**Multi Strand Gate**

G71802 2 Strand 26' (cattle)  
G71804 4 Strand 26' (sheep)

A low cost, all-in-one permanent electrified gate option with multiple live strands, for practically any width gateway. It's easy to setup and use - open/ close with one hand.



- Two or four strand option: Two strand for cattle and four strand for sheep
- Extendable tape lengths to fit desired gate width. Holds .5" tape (included) or 1.5" tape (clips included)
- Quick and easy to install. Simply attach to existing gate posts using supplied mounting hardware
- Simple, safe electrification as a live hook provides power to gate when closed and disconnects power when opened
- Easy to repair. If one strand breaks, simply change out the tape





## 34 Netting & Woven Wire



### ElectroNet

A201000

- 35"x 164' Roll.
- 8 conductive horizontal wires.
- White plastic vertical struts every 12".
- Roll complete with all posts, just unfold and set the posts.
- Impenetrable mesh fencing for sheep, goats, coyotes and dogs.

### Pos/Neg ElectroNet

A201200

- 35" Tall prefab fence with vertical struts every 12".
- 164' Long.
- For dry areas; good for sheep, goats and cattle.

### Poultry Net

A207015

- 48" High prefab electrical fence with 12 horizontal lines.
- 164' Long.
- ½" Diameter white PVC posts every 8'.
- Double 6" spikes on each post for support.



### Electra-Lock

Electrifiable Woven Wire Permanent Hi-Tensile Fence

A43024660 4 Wire 30" High

The cost savings are half of standard barbed wire construction.

This electrifiable woven wire fence comes in either 4 or 5 strands of hi-tensile, class 3 galvanized wire in 660' rolls. Specially designed lock knot holds vertical stays in place.

Installs with same corner and gate posts as standard barbed wire.

Recommended post spacing, depending upon terrain, is every 50' for 1 fiberglass post, 40' for wood posts and 25' for steel t-posts.



## Smart Fence 2 G70000

A quicker and easier all in one instant fence system, the Smart Fence 2 re-defines portable fencing.

- Instant portable fence system
- Easy to carry and store away
- Highly effective safe animal control
- System includes 4 wires, 10 posts, 328' length
- Compatible with Gallagher Energizers - Energizer is not included



## Horse Corral Kit

A155

A light weight (16 lb), complete in a bag kit for a 40' square corral. Quick and easy to assemble. Great for pack trips, horse shows or any event requiring a temporary enclosure.

- 1 B11 Energizer
- 1 Insul-Grip Gate Handle
- 1 Turbo Braid Spool
- 1 Ground Rod
- 10 Pigtail Posts



## Garden & Backyard Protection Kit

A600

This kit is an easy do-it-yourself electric fence that fences a 50' x 50' area with three adjustable wires. It is a perfect fit for a residential consumer that is interested in an easy and affordable way to protect their garden, landscape or new plantings. Essentially tool-free and can be installed in 1 hour or less. Energizer operates on common 'D' cell batteries - no electric outlet or extension cord is used.

- 8 - 48" x 3/8" Fiberglass Posts
- 2 Bags 3/8" Clips
- 1 Poly Wire 656'
- 1 - 3' Ground Rod
- 1 B10 Energizer






## 36 Fence Setups

Once you've decided on the type of fence you'll need - permanent, offset or temporary - check below to find out the best fence set up for the animal you want to fence.


### Cattle




### Permanent



### Pigs, Sheep, Goats






### Horses






If you are fencing more than one type of animal, it is best to choose the fence set up recommended for the smallest animal - to ensure they can't get under the bottom wire.

### Offset



### Temporary



# 38 Fence Tools & Fence Accessories

## FENCE TOOLS



**Fencing Pliers and Wire Cutter**  
G52200



Specifically designed for cutting, stripping and bending electric fence wire with minimum wire damage.

**Strainer Handle**  
G69530



Spring loaded ratchet strainer handle for quick adjustment of wire strainers (fits most varieties of ratchet strainers).

**In Line Wire Tightener Handle**  
A644



Tightener handle for Gallagher in-line wire strainers (G64304).

**Ratchet Wire Tightening Tool**  
G645004



In line wire tightener handle with super smooth ratchet action, to be used with Gallagher in-line wire strainers (G64304).

**Wire Twisting Tool**  
G523004



Ideal for installing clips on posts and droppers.

**4 Groove Wire Crimping Tool**  
A609



20" Long 4-groove, robust tool for crimping wire joiners and splicing wire.

**2 Groove Wire Crimping Tool**  
A609A



2 Groove, robust, tool for crimping wire joiners and splicing wire.

**High Tensile Wire Cutter**  
G524



9" long high tensile wire cutter.

**Poly/Turbo Wire Tensioner**  
AXLT8



Holds Poly Wire, Turbo Wire, .5" Poly Tape, .5" Turbo Tape and Turbo Braid.

**Warning Sign**  
G602404




A highly visible sign that warns that a fence is electrified. Required by law, to be used on boundaries and anywhere else public have access to a fence.

## FENCE TOOLS



**Pay Out Spinner**  
A308




A necessity for building permanent fence. The adjustable break keeps wire from overwinding and it attaches to a 2" receiver.

**HD Spinning Jenny**  
A309



Accommodates all standard wire sizes. Adjustable break keeps wire from overwinding.

**Spinning Jenny**  
A305



Accommodates up to a 100 lb. roll of wire.

**Wire Payout Spinner**  
A304



Adjustable break keeps wire from over-winding. Handles 4,000' and 2,640' spool of hi-tensile wire or 1,000' of Equine Fence.

**Drill Chuck**  
G71300



Drill chuck for #G66604 Screw-In Ring Insulators.

**Post Mount**  
G57110



Used to mount S10 & S16 Solar Energizers to Ring Top Posts.

**Post Driver**  
G52501



A specially designed driver for the Insulated Line Post.

**Line Post Sleeve**  
G53002 - 45"



The Line Post Sleeve prevents flex when driving Insulated Line Posts into hard ground.

**Pressure Plate**  
G54301



Prevents Insulated Line Post from sinking on hills due to fence tension on abrupt rises.

# Gallagher Weighing & EID Systems

Features	TSi 2	TW-3	TW-1	W210	W110
<b>OPERATION &amp; DATA COLLECTION</b>					
Manual and automatic weight locking options	▪	▪	▪	▪	▪
Internal rechargeable battery	▪	▪	▪	▪	
Compatible with Gallagher Loadbars and Heavy Duty Loadbars	▪	▪	▪	▪	
Assign visual tag against weight and EID number	▪	▪	▪		
Calculates average daily weight gain and carcass weight	▪	▪	▪		
Max number of weigh records	1,000,000+	1,000,000+	1,000,000+		
Number of traits recorded per session	20	3			
Individual animal notes and weight recorded	▪	▪	▪		
Multiple custom trait definitions (i.e. condition score, genetics etc.)	▪	▪			
Weight based calculations (eg dose weight)	▪	▪	▪		
Advanced customized calculations based on recorded animal data	▪				
Review full animal history in the yard	▪	▪	▪		
Manage treatments and associated withholding periods	▪	▪			
View animal pedigree information in graphical family tree	▪				
<b>DRAFTING</b>					
Maximum number of draft groups	9	9	9		
Liveweight drafting	▪	▪	▪		
Drafting by weight gain	▪	▪	▪		
Drafting by electronic ID number	▪	▪	▪		
On screen drafting statistics recorded	▪	▪	▪		
Automatic drafter interface	▪	▪	▪		
<b>CONNECTIVITY</b>					
Automatic load bar recognition & calibration	▪	▪	▪	▪	▪
Bluetooth connection to EID readers	▪	▪	▪		
WiFi connectivity	▪	▪	▪		
<b>SOFTWARE</b>					
Compatible with Gallagher Smartphone Apps	▪	▪	▪		
Animal Performance Software (APS) Standard for basic data analysis	▪	▪	▪		
Animal Performance Software (APS) Professional for advanced stock analysis	▪				



# 40 Entry Level Weigh Scales



## Weigh Scale Indicator W110

G01021

Easy collection of weights for livestock & general purpose weighing

Includes Weigh Scale Indicator, Mount Bracket & Loadbars

- Tough construction for all weather outdoor use
- Battery powered convenience (4 x AA batteries sold separately)
- Plug and play system enables easy portability
- 0-1,500 kg/3,300 lb weighing capacity
- 2 Year warranty



**Battery powered** - requires 4 "AA" batteries (sold separately)

**Easy to use** - modern design with large intuitive touch buttons

**Flexible weighing options** - three modes for weighing both static weights and livestock

**Robust** - loadbar connectors


**Durable** - protected cables to minimize damage in the yard/weighing site



**Loadbars Precalibrated** to indicator

**Galvanized steel chassis** construction for long life

**Fits most sizes of platform** with top-mounting holes



Use Gallagher scales and electronic identification readers to maintain records and prepare your livestock for shows & competitions.

## W210

G012504

Easy collection of weights for livestock & general purpose weighing

- Tough, shock and waterproof case
- Large labelled push buttons
- Large rotary dial
- Three weighing modes for quick and easy weighing: auto, manual and fine
- Compatible with most loadbars
- Internal rechargeable battery
- Large, easy to read display
- Simple operation




## W210 Package

AG210

Entry level weighing system for producers. Get it all in one package deal!

Includes: W210 Indicator, Alleyway Loadbars, and Platform.

See page 44 for Alleyway Loadbar and Platform details.



**Weigh scales offer a quick return on investment, that is usually seen within the first year of installation.**



# 42 Weighing, Data Collectors

## TW-1 Weigh Scale Indicator

G02601

Simple to operate, touch screen weigh scale. Collect data to optimize animal performance.

- Bright, high clarity, daylight readable color touch screen
- Simple to use interface
- On screen product manual
- Flexible mounting options
- Multiple connectivity options
- Set animal notes and alerts
- Draft by weight, weight gain or EID list
- Built in graphs and data analysis at your fingertips
- 1 year warranty

**Market leading touch screen technology** - Full color, outdoor readable touch screen. Large 7" screen, shows weight and gain information in an easy to read font.

**Animal data analysis on device** - Shows individual weight gain graphs, as well as weight distribution plots for all animals within a weighing session.

**Ultimate user experience** - Design of the scale and execution of common tasks have been rigorously tested to ensure the scale is easy to navigate and that we are able to deliver the best customer experience on the market.

**On board help, 24/7** - The entire product manual is loaded into the product. No matter where you are, or what you are trying to do help is only one click away.

**Animal notes and note alerts** - Record notes against animals on the spot for later review. Notes alert the operator when the animal's tag is read.

**Tough, rugged exterior** - Toughened, scratch proof glass screen makes it suitable for all environments.



**Flexible mounting options** - Easy to use sitting flat, or mounted to a vertical surface. The adjustable mounting bracket allows you to easily tailor the viewing angle for optimum visibility.

**Flexible connectivity options** - Whether connecting to drafters or readers via a serial cable, to a PC via USB or utilizing the Bluetooth and WiFi wireless options, the TW-1 has every option available.





## TW-3 Weigh Scale Indicator & Data Collector

G02603

Simple to operate, touch screen weigh scale. Collect data to optimize animal performance.

### All the features of the TW-1 plus:

- Full QWERTY keyboard
- Record weight, life data and traits. Ideally suited to producers waiting to record and review more information than simply weight of their animals. Can record up to three traits per session
- Record treatments on the spot. Animals can be weighed and administered the correct dose rate and the information recorded on the weigh scale at the time of treatment
- You can draft by weight or recorded trait and/or life data. Recorded data draft examples: bred, preg or open, lot or pen, property, breed, sex, color or sale

**Market leading touch screen technology** - Full color, outdoor readable touch screen.

**On board help, 24/7** - The entire product manual is loaded into the product. Help is only one click away.

**Record treatments on the spot** - Animals can be weighed and administered the correct dose rate, all recorded on the weigh scale at the time of treatment.

**Animal notes and note alerts** - Record notes against animals on the spot for later review. Notes alert the operator when the animal's tag is read.

**Animal data analysis on device** - Shows individual weight gain graphs, as well as weight distribution plots for all animals within a weighing session.

**Record life data and traits** - Ideally suited to producers wanting to record and review more information than simply weight on their animals. Can record up to 3 traits per session.

**Ultimate user experience** - Execution of common tasks have been rigorously tested to ensure that we are able to deliver the most customer friendly experience on the market.

**Tough, rugged exterior** - Operator ready, tough design.



**The TW-1 & TW-3 come in an heavy duty bag, conveniently packaged and ready to go** - Just connect to your Gallagher loadbars and you have everything you need to start weighing:

- Tough and convenient Gallagher carry case
- Mounting bracket
- Micro-fibre screen cloth
- Battery charging cable
- 110v charging cable
- USB drive loaded with APS software
- USB cable for data transfer to PC



# 44 Weighing, Data Collectors

**TSi 2**

G01901

**FASTER PROCESSOR  
MORE MEMORY  
IMPROVED SCREEN**

An animal weighing and data collection system for improved livestock management and performance. The TSi 2 provides immediate access to detailed animal information, anywhere, at any time - in the sale barn, the office or on the ranch.

**Intuitive software** - Supplied with award-winning Animal Performance Software (APS Professional), for analysis and reporting to provide virtually any information you need.

**Rugged exterior** - Tough ranch/farm ready design for all-weather use.

**Rapid, accurate, automatic weight capture.**

**Customizable sessions** - Easily customize weighing and data recording sessions to collect specific traits, activities, notes etc.

**Simple recording and retrieval** - Collection of comprehensive data and retrieval of information at the touch of a button, while in the yard.

**Exceptional connectivity** - Bluetooth wireless connection and full integration with loadbars, EID readers, auto drafters and other management software.

**Easily transfer data** - WiFi enabled to allow upload of data directly to web and share with third parties.

**Significant memory capacity** - Entire life history of all animals stored for on-site viewing - over one million animal records can be stored.

**Comprehensive drafting** - Draft by weight, EID number or custom defined rules.

**Touch screen** - Full color outdoor readable touch screen with large touch buttons.



**ANIMAL PERFORMANCE SOFTWARE (APS PROFESSIONAL INCLUDED)**  
Analyze data and upload in three easy steps.

**Comes with carry case, memory stick and mounting bracket.**  
Dimensions: 14" (w) x 11" (d) x 3.5" (h) 29 lbs (excluding power supply)



## Alleyway Loadbars

G06000



- 4,400 lb weighing capacity in 23" length
- Rugged galvanized steel chassis
- Bottom feet-mounting holes extend beyond top covers for ease of bolting down
- Slotted top-mounting holes fit most sizes of platforms
- 19.6' long, tough polyurethane loadbar cables with spring wire protection
- Fitted with high quality, moisture proof connectors
- Fully water resistant
- No rubber mounts
- 2 Year warranty

## Heavy Duty Loadbars

G06300



- 7,700 lbs weighing capacity in 39" length
- High capacity load cells are able to withstand large shock loads
- Heavy galvanized steel chassis construction to withstand the harshest environments
- Bottom feet-mounting holes extend beyond top covers for ease of bolting down
- 19.6', tough polyurethane loadbar cables with spring wire protection
- Fitted with high quality, moisture proof connectors
- Fully water resistant
- No rubber mounts
- Designed for a manual squeeze chute
- 2 Year warranty

## Super Heavy Duty Loadbars

G06400



- All of the features of the Heavy Duty Loadbars but have 9,900 lbs weighing capacity in 39.3" length. These loadbars are made from galvanized steel and are powder coated
- Designed for manual chute or hydraulic chute
- 2 Year warranty

## Heavy Duty Weigh Feet Kit

G05420




- Five tough, stainless steel weigh feet for easy mounting under cattle chute and custom platforms. One extra loadcell supplied in kit for easy replacement and no down-time
- 11,000 lbs weighing capacity
- Fast and easy loadcell replacement without major lifting
- High accuracy corner to corner performance for demanding weighing requirements
- Designed for manual chute or hydraulic chute
- Not compatible with W210

## Aluminium Platform

G05900

- A high-strength platform designed to fit Gallagher 4,400 lbs. alleyway loadbars and most other branded loadbars
- Combine strength and portability to reduce the time and hassle involved in setting up weighing sessions
- Dimensions: 86.5" long, 24.5" wide; Platform weighs 49 lbs.



## Smart Reader Electronic Controllers



G03113

- HDX and FDX-B, ISO and NAIT Tag compatible
- No antenna tuning required
- Can be used with either antenna panel below

### R Series Electronic Controller

- Electronic controller for livestock identification
- Requires external 12 volt power source (not included)



G03111

### BR Series Electronic Controller

- Battery powered electronic controller for livestock identification
- Internal rechargeable battery
- Easy to read battery charge indicator
- Internal memory stores 20,000 tags
- Tag counter display screen records animals scanned
- Download stored records to computer
- Replacement battery A728



Cattle automatically identified by BR Series as they enter the handler.



BR Series automatically provides ID number to Weigh Scale Indicator enabling accurate collection of individual sheep weights.



G031424

G03121

### Smart Reader Panel Antennas

- Suitable for walk past identification applications
- HDX and FDX-B ISO compliant panel
- Waterproof antenna panel
- Mounting hardware supplied
- Can be used with either electronic controller above

#### Large Panel Antenna

Dimensions: 23.5" W x 51.5" H

#### Small Panel Antenna

Dimensions: 15.75" W x 23.5" H



Integrated BR Series and Weigh Scale Indicator system on cattle handler.

## SCALE ACCESSORIES

### 20' Loadbar Extension Cables

- 4,400 lbs Loadbar (G05000)
- 7,716/9,900 lbs Loadbar (G05100)
- 20' long, tough polyurethane loadbar cables
- Fitted with high quality, moisture proof connectors



### 15' Double Antenna Cables

- Double antenna cables designed to link two panels to one reader.
- G05606 - Use with small and large antenna panels.



### 110V Adaptor 2M1695

### Scale Bracket 4G2209

Gallagher Hand Held EID Tag Readers are the perfect tool for portable EID data collection.

## HR5

G03303

Record, edit and customize data anywhere. Now connects to Apple over Wi-fi.



**Compatibility** - Compatible with Gallagher and other brands of EID capable weighing data collectors.

**Large easy to read screen - 2.8"** backlit colour display with hi-resolution large graphics - easy to read indoors and out.

**Fast and continuous reading** - with one trigger click.

Records weights and displays weight gain. (HR5)

**Full texting style keypad** for easy on site data entry.

**Market leading ergonomic design** with long reach and hand guard for maximum operator safety.

**Simple connectivity** - includes PC and charging cables.

**Receive animal weights from TW-1 and TW-3 via Bluetooth (HR5).**

**Pair with other devices** - Easily search and connect via Bluetooth to other devices.

**LED, vibration and beeper** - to show tag read successful.




**FREE ANIMAL DATA TRANSFER APP**  
Transfer animal data to NAIT using your Gallagher Hand Held EID Tag Reader and Android or Apple phone.

**ANIMAL PERFORMANCE SOFTWARE (APS STANDARD INCLUDED)**

## HR4

G03302

Easy recording of pre-defined animal data against EID tag numbers.

- Large display clearly shows visual ID and EID tag numbers to confirm the correct animal information is being collected
- Choose multiple traits to record against each animal such as breed, sex, condition score and pregnancy status
- Sort group name is highlighted on the screen for easy reference with optional group colors
- View past traits, activities and life data recorded against an animal
- Compatible with Gallagher Android Animal Data Transfer App





# 48 Stock Prods & Accessories

Strong, safe and instant power for an effective, durable and inexpensive option to keep livestock moving, wet or dry.

## Heavy Duty SG240 Two year warranty



Sealed replaceable motor

Moisture proof one piece handle

Balanced and comfortable hand grip

Safety wrist strap with button locking clip

## Standard SG150 One year warranty



Safety wrist strap

Disposable batteries included

## Stock prod shafts

32"  
SG082



36"  
SG091



42"  
SG107



- Large attachment nut to help reduce breakages
- Brass contact points for positive results
- One year warranty

\*Note: Length includes handle

## 54" Sorting Pole SG006

- Orange fiberglass shaft
- Heavy duty rubber tip
- Golf grip handle



## 48" Sorting Paddle SG007

- Noise makers inside
- Golf grip handle



## Handy Shock SG001

- Only 9.4 ounces
- Pocket size
- Includes 4 "AA" batteries
- 1 Year warranty

**QUALITY  
WATER  
PROMOTES  
LIVESTOCK  
RATE OF GAIN**

# Miraco Watering Tank Systems

Miraco has been offering healthy, clean, fresh livestock water systems to producers since 1974.



Miraco tanks can withstand cold temperatures without freezing



5 Year warranty offered on all Miraco Tanks



Poly construction makes these tanks durable. Multiple color options available on select tanks

Miraco perfected energy-free watering systems and was the first to manufacture automatic livestock waterers from poly materials. Join other livestock producers who enjoy the innovative features of Miraco Livestock Watering Systems.



## E-Fount Waterers

E-Founts are the most economical electric heat waterers available today.

All E-Founts come equipped with a 75 watt heat element and thermostat. E-Founts only require 4 kilowatts of electricity during a week of -25 F temperatures.

## MiraFount Waterers

MiraFount Tanks were the first livestock tanks in the world to be developed energy free. These innovative tanks have 2-3" of urethane insulation and have extra installation above the valve area. Water stays cool in warm temperatures and does not freeze in cold conditions.



Our real business is you.

# 50 Miraco Livestock Waterers

## MiraFount A3390



Capacity: 150 head beef  
60 head dairy

Gallons: 44

Specifications: Two 10" openings/  
10.75" ball closures

Dimensions: 43"x 29"x 27.5" (L x W x H)

Weight: 129 pounds (58 kg)

Energy Free

- Split top-end panels can be easily removed to help get new cattle started fast. Or, remove the panels to provide more capacity for a few extra head. Stainless Steel anchor bolts are included

## E-Fount A3390-E



Energy Efficient  
Heat Element: 75 Watts

## MiraFount A3330



Capacity: 50 head beef  
25 head dairy

Gallons: 15

Specifications: One 8.75" opening/9" ball closure

Dimensions: 28"x 26"x 21" (L x W x H)

Weight: 57 pounds (26 kg)

Energy Free

- Stainless Steel anchor bolts are included

## E-Fount A3330-E



Energy Efficient  
Heat Element: 75 Watts

## MiraFount A3465



Capacity: 100 head beef  
40 head dairy

Gallons: 20

Specifications: Two 9.25" openings/10" ball closures

Dimensions: 36"x 24"x 18" (L x W x H)

Weight: 79 pounds (36 kg)

Energy Free

- Stainless Steel anchor bolts are included

## E-Fount A3465-E



Energy Efficient  
Heat Element: 75 Watts

## MiraFount A3345-S



Capacity: 75 head beef  
30 head dairy

Gallons: 30

Specifications: One 10" opening / removable top

Dimensions: 29" x 31" x 26.5" (L x W x H)

Weight: 95 pounds (43 kg)

Energy Free

- Stainless Steel anchor bolts are included

## E-Fount A3345-E



Energy Efficient  
Heat Element: 75 Watts

**MiraFount** A3354-S

Energy Free

Capacity: 200 head beef  
90 head dairy

Gallons: 70

Specifications: Four 9.5" openings / 10.75" ball closures

Dimensions: 57.5" x 32.5" x 27" (L x W x H)

Weight: 152 pounds (69 kg)

- Removable top-end panels help get new cattle started fast or provide more capacity for a few extra head

**E-Fount** A3354-SEEnergy Efficient Heat Element:  
Two 75 Watt Heaters**MiraFount** A3340

Energy Free

Capacity: 100 head sheep

Gallons: 15

Specifications: Four 6" openings / 7" ball closures

Dimensions: 28" x 26" x 20" (L x W x H)

Weight: 57 pounds (26 kg)

- Stainless Steel anchor bolts are included

**E-Fount** A3340-EEnergy Efficient  
Heat Element: 75 Watts**MiraFount** A3410

Energy Free

Capacity: 100 market hogs  
50 sows

Gallons: 6


Specifications: Two lift up lids / 10" openings

Dimensions: 34" x 19" x 16.5" (L x W x H)

Weight: 57 pounds (26 kg)

Drinking Height: Low drinking profile for small pigs

- Two large drain holes with rubber plugs for easy cleaning

**E-Fount** A3410-EEnergy Efficient  
Heat Element: 75 Watts**MiraFount** A3410-4

Energy Free

Capacity: 200 market hogs  
100 sows

Gallons: 15

Specifications: Four lift up lids / 10" openings

Dimensions: 34" x 36.5" x 16.5" (L x W x H)

Weight: 98 pounds (45 kg)

Drinking Height: Low drinking profile for small pigs

- Two large drain holes with rubber plugs for easy cleaning

**E-Fount** A3410-4EEnergy Efficient  
Heat Element: 75 Watts



# 52 Miraco Livestock Waterers

## MiraFount

A3370-S



Capacity: 250 head beef  
120 head dairy  
200 cow/calf units

Gallons: 100

Specifications: Six 9.5" openings/ 10.75" ball closures

Dimensions: 57.5"x 45.5"x 28" (L x W x H)

Weight 216 pounds (98 kg)

- Features removable end panels to help get new cattle started fast or to provide more capacity for a few extra head. Two valves are provided for fast recovery



## Lil'Spring Tank Waterers

Features:

- One-piece body polyethylene construction
- No sharp edges
- Tough high impact resistant "Rockite" material to stand up to livestock abuse
- Resistant to corrosion
- Removable dome for quick and easy access to the valve area
- 2-3" urethane foam insulation
- Molded base unit anchors (stainless steel anchor bolts are included with all models)
- Sloped bottom for easy cleaning
- Sealed bottoms
- Color options are available
- Optional heater may be added

## Lil'Spring

A2700



Capacity: 100 head sheep

Gallons: 6

Dimensions: 28.75" x 17.5" x 24.5"  
(L x W x H)

Weight: 40 pounds (18.15 kg)

Heat: Optional, 250-watt submersible heater (A160)

## Lil'Spring

A2800

Capacity: 20 head beef  
20 head horses

Gallons: 4

Dimensions: 20" x 16" x 19"  
(L x W x H)

Valve: Miraco automatic plastic

Weight: 40 pounds (18 kg)

Heat: Optional 110-volt, 250-watt submersible heater (A160)



- 200 psi hose w/shut off valve included
- Attractive design; five color options: Gray, Standard Blue, Black or Hunter Green

## Lil'Spring

A2900

Capacity:	40 head beef 40 head horses
Gallons:	6
Dimensions:	30.5" x 16.5" x 19" (L x W x H)
Valve:	Miraco automatic plastic
Weight:	48 pounds (18 kg)
Heat:	Optional 110-volt, 250-watt submersible heater (A160)



- 200 psi hose w/shut off valve included
- Anchor bolts are included
- Attractive design; five color options: Gray, Standard Blue, Black or Hunter Green



*"I'm only interested in the best for my horses and Miraco watering systems are the best. These are strong, durable systems ergonomically designed to make it easy for the horse to get access to drink. Miraco products are also safe for the horse, and that's really important to me."*


Curt Pate

World-renowned South Dakota horse trainer and clinician, film consultant and author

## Recommended Installation Diagram

A 1" diameter line is recommended. The line should be buried 4' deep or 1' below the published frost line depth in your region.

Miraco recommends installing on a concrete platform that provides a 4-6" step and 18" around the perimeter of the unit. The concrete platform must be level to ensure optimal performance.



# 54 Miraco Livestock Waterers

## Lil'Spring

A3000



Capacity: 30 head beef  
30 head horses  
50 head sheep

Gallons: 5

Dimensions: 24" x 22" x 15" (L x W x H)

Valve: Miraco automatic plastic

Weight: 48 pounds (22 kg)

Heat: Optional 110-volt, 250-watt submersible heater (A160)

- 3" offset drain
- Bottom drain for inside use. 2" threaded fitting underneath for PVC plumbing
- Installs easily on most existing concrete pads.
- Stainless steel anchor bolts included

## Lil'Spring

A3100DS



Capacity: 100 head beef  
50 head dairy

Gallons: 8

Dimensions: 36" x 22" x 22" (L x W x H)

Valve: Miraco automatic plastic

Weight: 75 pounds (34 kg)

Heat: Optional 110-volt, 250-watt submersible heater (A160)

## Lil'Spring

A3200



Capacity: 150 head beef  
75 head dairy

Gallons: 25

Dimensions: 48" x 24" x 30" (L x W x H)

Valve: Miraco automatic plastic

Weight: 98 pounds (45 kg)

Heat: Optional 110-volt, 250-watt submersible heater (A160)

- Large access panel for easy access to valve area with spring load clips
- 3" offset drain
- Access panels at both ends
- Installs easily on most existing concrete pads
- Constant flow available
- Stainless steel anchor bolts included



**Lil'Spring**

A3500



Capacity: 225 head beef  
110 head dairy

Gallons: 40

Dimensions: 42" x 42" x 26" (L x W x H)

Valve: Miraco automatic plastic

Weight: 145 pounds (65 kg)

Heat: Optional 110-volt, 500-watt submersible heater (A162)

- 168" Drinking space
- Quick release valve access cover
- Diagonal valve compartment lets more cattle drink
- 24" hook-up hose with shut off valve
- Stainless steel anchor bolts
- 2 Bottom drains
- Teflon coated

**EquiFount features smooth rounded edges for safety with minimum intrusion on stall space**

**EquiFount Corner Mount**

A1100



Dimensions:  
16" x 16" x 14"  
(L x W x H)

**EquiFount Wall Mount**

A1200



Dimensions:  
16" x 16" x 14"  
(L x W x H)

Capacity: 1 Horse

Gallons: 1

Drinking Height: 26" (66 cm)

Heat: Optional 110-volt, 250-watt submersible heater (A276)

- Smooth rounded edges for safety
- Durable 100% polyethylene construction; urethane foam insulation
- Easy valve access; one-screw, quick water level adjustment
- Four-bolt installation
- Plumb from above or below
- Ample drinking space; plentiful water supply with minimal waste
- Large easy drain; no disassembly required
- Attractive design; five color options: Gray, Standard Blue, Black or Hunter Green

**EquiFount Insulated Ext Tube**

A834-5



- Cold barns are not a problem for EquiFount waterers. This insulated extension tube allows water line to enter from below without freezing
- Rubber plug can be removed for access to water shut-off valve



# 56 Miraco Livestock Waterers

**BigSpring Waterers are the preferred choice of cattle & dairy producers**

## BigSpring

A6000



Capacity: 250 head beef  
100 head dairy  
Gallons: 60  
Dimensions: 90"x 33"x 24" (L x W x H)  
Weight: 215 pounds (97 kg)

- Optional 500 watt heater (110 or 220 volt - A162)
- Optional constant flow (30 or 60 gallon level)
- Water spray for attracting new cattle to water
- 3" (8 cm) drain hole with rubber plug for rapid cleaning
- Removable dome for easy access to valve area
- Spring-loaded clips - no wrenches required
- Rubber gasket for air-tight dome seal
- End panel access
- For cleaner water, neckrail to prevent cattle from standing in the water

## BigSpring

A6100



Capacity: 110 head dairy  
Gallons: 60  
Dimensions: 80"x 36"x 24" (L x W x H)  
Weight: 205 pounds (93 kg)

- Optional 500 watt heater (110 or 220 volt - A162)
- Flat back design fits flush with the wall
- Center between stalls or place one on each
- Curved front for full, easy access - no wasted space
- Pour foundation with a curve for easier cleaning
- No wrenches required for valve compartment access
- Rubber gasket for air-tight dome seal
- Recommended installation on 10" concrete riser or with neck rail
- Optional gravity fill assemble available
- Stainless steel anchor bolts included
- For cleaner water, neckrail to prevent cattle from standing in the water

## BigSpring

A6200

Capacity: 200 head beef  
100 head dairy  
Gallons: 60  
Dimensions: 84" x 22" x 22" (L x W x H)  
Weight: 170 pounds (77 kg)

- Designed for free stall barns
- Flat back design for flush fit with a wall or panel
- Three access panels and no wrenches required for valve compartment access
- Two large 3" drains, severe slope for quick draining
- Rubber gasket for air-tight dome seal
- Optional 500 watt heater (110 or 220 volt - A162)



- For cleaner water, neckrail to prevent cattle from standing in the water
- Optional gravity fill assembly available

**BigSpring**

A6300

Capacity: 300 head beef  
150 head dairy  
Gallons: 110  
Dimensions: 144" x 22" x 22" (L x W x H)  
Weight: 275 pounds (125 kg)  
Heat: Optional 500 watt heater (110 or 220 volt - A162)



**BigSpring**

A6400

Capacity: 250 head beef  
125 head dairy  
Gallons: 90  
Dimensions: 120" x 22" x 22" (L x W x H)  
Weight: 230 pounds (104 kg)  
Heat: Optional 500 watt heater (110 or 220 volt - A162)

**Water Tank Accessories**

**Hook Up Kits (A158)** 2' rubber hose (200 psi) with shut off valve



**Underground Shut Off Kit (A399-5)** Comes with drain back

**Insulated Heat Tubes (A834)**

Outside Dimensions 14" x 30", Insulation is 2"  
Weight: 16 pounds (7 kg)

Highly insulated tube shields incoming ground water from cold as it passes through the frost level. Polyethylene construction ensures years of trouble free use. One 20" tube and 3' of 12" plastic drainage tile provide sufficient heat in most locations. For northern locations two 30" heat tubes may be required.



**Automatic Valves (A336)**

GPM 14, Low pressure 5 - 40 psi

**Automatic Valves (A521)**

GPM 12.5, High pressure 40 -80 psi

**Automatic Valves (A519)**

GPM 6, Super high pressure 80 - 90 psi



**Pet Waterer**

A1000

- All polyethylene construction for easy cleaning
- No buildup of bacteria or algae
- Full polyurethane foam insulation
- 5 gallon reservoir - add ice during hot weather
- Bowl refills automatically - no moving parts
- Optional 250 watt heater assembly (A250)



**Heaters, Cable & Floating Tank Valves**

**250 Watt Immersion Heater (A160)**

Has a built-in thermostat 550  
Teflon coated, 1-Yr Warranty

**500 Watt Immersion Heater (A162)**

110 Volt or 220 Volt  
Teflon coated, 1-Yr Warranty



**5' Cable Line Heater (A919-5)**

**8' Cable Line Heater (A919-8)** - 110 Volt or 220 Volt

**Gallagher .75" Water Tank Brass Valve with Float (AQ100B)**



**Gallagher .75" Water Tank Poly Valve with Float (AQ400P)**



**1" Water Tank Poly Valve with Float (AQ500P)**

# 58 Icon Reference





## POWER

- |   |   |  |  |  |
|---|---|--|--|--|
|  12v battery included                  |  AA batteries included       |  9v battery included          |  Rechargeable battery             |  Rechargeable 12v battery |
|  Stored energy                         |  12v battery powered         |  Mains powered                |  Battery not included             |  Area powered             |
|  Mains Power Adapter included /capable |  Mains/battery powered       |  Solar powered/ solar capable |  Energizer Controller             |  Remote included /capable |
|  Solar/12v battery powered             |  LCD display                 |  Color                        |  Alarm capable                    |  Energizer                |
|  Low power option                      |  Output voltage bar graph    |  Battery life check           |  Rechargeable 6v battery included |  |
|  Smartpac Remote included/capable      |  XR1 Remote included/capable |  SMS capable                  |  Time saving                      |  |
|  Adjustable voltage                    |  Battery save options        |  Battery save options         |  Fence Monitor included/capable   |  |

## CONSTRUCT

- |  |  |   |   |
|--|--|---|---|
|  Single foot                |  Double foot              |  Compression spring    |  High visibility flag included |
|  Offset length              |  Use on wood posts        |  Use on T posts        |   |
|  Use on steel posts         |  Use on rod posts         |  Use on concrete posts |   |
|  Use on steel treadin posts |  Use on high tensile wire |  Use on steel post     |   |

## CONDUCT

- |   |   |   |
|---|---|---|
|  Wire diameter         |  Length                    |  Reel gear ratio |
|  Stripes deter animals |  Tape width                |  Height          |
|  Cable wire diameter   |  Insulated Handle included |   |



Gallagher is committed to helping producers do and achieve more with educational clinics & many quality products that may be found at approved Gallagher dealers where you will always get professional advice and great support.

Drop in and visit your trusted Gallagher dealer. While you are there, be sure to ask about upcoming fencing and grazing clinics in your area.

You can locate your nearest dealer on our website at:  
[www.GallagherUSA.com](http://www.GallagherUSA.com)





